


PRODUCT CATALOG

3x36 Swaged

- ▶ Increased surface area
- ▶ Better rope contact with sheaves and on drums
- ▶ Fatigue-resistant



These 3 strand ropes are ideal for pulling lines in electrical transmission line construction. Rotary swaging the rope results in an exceptionally compact rope cross-section. This increases surface area, which improves rope contact with sheaves and on drums, thereby providing greater resistance to surface wear and abrasion while reducing wear on sheaves. The smooth surface also helps reduce wear on underground conduits. Lengths may be fitted with flemish-eye ends.

3x36 Swaged Strength and Weights Chart

Diameter (in)	Approx. Wire Weight (lb/ft)	Minimum Breaking Force (tons of 2000 lbs.)
1/2	0.53	14.8
9/16	0.66	18.6
5/8	0.83	22.9
3/4	1.19	32.7
7/8	1.69	44.3
1	2.09	57.5

Union, a WireCo WorldGroup brand, produces wire rope for a variety of applications – each with their own exacting specifications. We employ the most experienced, talented, licensed engineers in the industry to design solutions for your application. Eight WireCo WorldGroup manufacturing operations and seven distribution centers in North America, plus manufacturing facilities in Mexico, Germany and China, give our customers unparalleled support and global reach. Find out for yourself why Union wire ropes have proven themselves time and time again in the field. **Union: Tested, Tough & True.**

» [view searchable product catalog](#)