

STUD END MS-21259

TUF-GRIP Stud Ends are made with grade 303Se or 305 stainless steel to give you dependable service. It's made to MIL-DTL-781 specifications and drilled for a tie wire. Its length is measured from the outer end of the thread. Other sizes are available on request.

You need to specify right-hand or left-hand thread as follows:

- MS-21259-12RH is 3/8 inch diameter wire rope with right-hand thread stud end.
- MS-21259-12LH is 3/8 inch diameter wire rope with left-hand thread stud end.

SW702 FOR NON-MILITARY APPLICATIONS

Dimensions for Stud End

Dash no.	Rope dia.	B-THD.	D	T	A _S	Afterswage L _S
2	1/16	No. 6 - 40	.188	1.045	.138	2.65
3	3/32	No. 10 - 32	.250	1.204	.190	3.00
4	1/8	1/4 - 28	.313	1.376	.219	3.59
5	5/32	1/4 - 28	.313	1.376	.250	3.97
6	3/16	5/16 - 24	.375	1.453	.313	4.17
7	7/32	3/8 - 24	.438	1.625	.375	4.81
8	1/4	3/8 - 24	.500	1.750	.438	5.24
9	9/32	7/16 - 20	.625	1.875	.500	5.75
10	5/16	1/2 - 20	.688	2.000	.563	6.27
12	3/8	9/16 - 18	.750	2.250	.625	7.06
14	7/16	5/8 - 18	.812	2.500	.688	7.91
16	1/2	5/8 - 18	.875	2.500	.750	8.75

All dimensions are in inches. Other sizes are available on request. Available in two-sided or six-sided wrench flats.

