

TURNBUCKLE END MS-21260

You'll see many similarities between the TUF-GRIP Stud End and Turnbuckle End. Each is made with the same material – grade 303Se or 305 stainless steel. Each is made to the same MIL-DTL-781 specifications. Each is also drilled for a tie wire. The length of each is also measured the same way – from the outer end of the thread. In both cases, you may specify other sizes if desired.

When ordering, please specify right-hand or left-hand threads as follows:

- MS-21259-12RH is 3/8 inch diameter wire rope with right-hand thread.
- MS-21259-12LH is 3/8 inch diameter wire rope with left-hand thread.

Dimensions for Turnbuckle End

Dash no.	Rope dia.	B-THD.	C	D	T	A _S	Afterswage L _S
2	1/16	No. 6 - 40	.092	.188	.375	.138	3.67
3	3/32	No. 10 - 32	.133	.250	.500	.190	3.86
4	1/8	1/4 - 28	.195	.313	.563	.219	4.28
5	5/32	1/4 - 28	.195	.313	.625	.250	4.66
6	3/16	5/16 - 24	.245	.375	.750	.313	4.78
7	7/32	3/8 - 24	.306	.438	.875	.375	5.21
8	1/4	3/8 - 24	.306	.500	.875	.438	5.52
9	9/32	7/16 - 20	.361	.625	1.000	.500	5.90
10	5/16	1/2 - 20	.406	.688	1.000	.563	6.30
12	3/8	9/16 - 18	.476	.750	1.125	.625	7.01
14	7/16	5/8 - 18	.538	.812	1.250	.688	7.94
16	1/2	5/8 - 18	.538	.875	1.250	.750	9.28

All dimensions are in inches. Other sizes are available on request.

