

CLOSED SOCKET SW-709

Both of these sockets are attached in the same plane as the fitting on the other end of the assembly unless you specify otherwise. Measure the length of each from the center of the pin hole.

Pins and cotters are standard for the open sockets, but you may order these sockets without pins if you wish.

EQUIVALENT TO SA164 SERIES

Dimensions for Closed Socket

Dash No.	Rope Dia.	D	E	F	A _s	X	Afterswage L _s
8	1/4	1 3/8	1/2	0.76	0.46	3/4	3 7/8
10	5/16	1 5/8	11/16	0.88	0.71	15/16	5
12	3/8	1 5/8	11/16	0.88	0.71	15/16	5
14	7/16	2	7/8	1.07	0.91	1 1/8	6 3/8
16	1/2	2	7/8	1.07	0.91	1 1/8	6 3/8
18	9/16	2 3/8	1 1/8	1.28	1.16	1 5/16	8 1/16
20	5/8	2 3/8	1 1/8	1.28	1.16	1 5/16	8 1/16
24	3/4	2 7/8	1 5/16	1.49	1.42	1 5/8	9 9/16
28	7/8	3 1/8	1 1/2	1.73	1.55	1 3/4	11 3/16
32	1	3 5/8	1 3/4	2.11	1.80	2 1/16	12 3/4
36	1 1/8	4	2	2.37	2.05	2 1/4	14 1/8
40	1 1/4	4 1/2	2 1/4	2.62	2.30	2 9/16	15 15/16
44	1 3/8	5	2 5/16	2.62	2.56	2 13/16	17 1/2
48	1 1/2	5 3/8	2 9/16	2.87	2.81	3 1/8	18 7/8
56	1 3/4	6 1/4	3 1/16	3.63	3.06	3 9/16	22 3/16
64	2	7 1/4	3 5/16	3.88	3.56	4 1/8	25 1/2

All dimensions are in inches.

